



1ST CHOICE FOR PROFESSIONALS WORLDWIDE

Visit our website:



Henkovac

Het Sterrenbeeld 36
5215 ML 's-Hertogenbosch
The Netherlands

Phone: +31 (0) 73 627 12 71
Email: sales@henkovac.com
www.henkovac.com

Copyright Henkovac 2024



Double Chambers

D1 - D3 - D4 - D5 - D6



1ST CHOICE FOR PROFESSIONALS WORLDWIDE



D1



D3



D4



D5



D6

Specifications

Seal	Double	Double
Machine dimension mm	1440 x 900 x 1205	1865 x 1100 x 1170
Standard voltage	400 - 3 - 50 Hz	400 - 3 - 50 Hz
Digital Time Control	10 Programs	10 Programs
Pump Capacity	63 m3	160 m3
Average weight	425 kg	600 kg

Options










Filler plates / Liquid filler plates	Yes	Yes
Sensor control	Sensor / H ₂ O	Sensor / H ₂ O
Soft Air	Soft Air	Soft Air
Seal	Trenn (pre-cut) / 1-2 / Bi-Active	Trenn (pre-cut) / 1-2 / Bi-Active
Gas	Gas	Gas
Pump upgrade	100 or 160 m3	300 m3
Power Consumption	3.0 kW - 3.5 kW - 5.0 kW	5.0 kW - 8.0 kW

ALUMINUM COVER | CHAMBER

Double	Double	Double
2050 x 1265 x 1185	2460 x 1100 x 1180	1345 x 720 x 1040
400 - 3 - 50 Hz	400 - 3 - 50 Hz	400 - 3 - 50 Hz
10 Programs	10 Programs	10 Programs
160 m3	160 m3	40 m3
720 kg	782 kg	280 kg

Yes	Yes	Yes
Sensor / H ₂ O	Sensor / H ₂ O	Sensor / H ₂ O
Soft Air	Soft Air	Soft Air
Trenn (pre-cut) / 1-2 / Bi-Active	Trenn (pre-cut) / 1-2 / Bi-Active	Trenn (pre-cut) / 1-2 / Bi-Active
Gas	Gas	Gas
300 m3	300 m3	63 or 100 m3
5.0 kW - 8.0 kW	5.0 kW - 8.0 kW	2.5 kW - 3.0 kW - 3.5 kW

Seal configurations



Double Chambers

1ST CHOICE FOR PROFESSIONALS WORLDWIDE

